

# Datasheet - *Permaplay*

## P49KDTAB01TSFS (49" android touch screen floor stand)

### Product Specification

CPU	Rockchip RK3288, quad-core Cortex-A17, GPU Mali-T764.
Frequency	2.2 GHz
RAM	DDR3 2G/(4G optional)
Internal Storage	EMMC 8GB/(16G/32G Optional), supports NAND FLASH.
Display	Resolution: 1920x1080/49"
	Contrast ratio: 5000:1
	Luminance: 400cdm2
	Aspect Ratio: 16:9
	Viewing angle: 178x178
Touch panel	10-Points capacitive touch panel
Network Support	RJ45 port, 10/100/1000M Ethernet.
WiFi	Built-in WiFi & supports Wi-Fi 802.11b/g/n/ ac.
BT module,	BT4.0.
Image rotation	Support 0°, 90°, 180°, 270° manual rotation.
Clock	Built-in battery power supply.
Interface Devices	USB interface camera supports up to 200W pixels.
	USB Host x1, USB OTGx1
	Extended 3 serial ports supports for external devices connected to the module. (NFC module, printer, card reader, etc.)
	TF card, supports up to 32GB.
	HDMI 2.0 output.
Audio	MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP.
Video	Support H.264, MPEG2, VP6, VP8, MVC, 2160P@24FPS. YouTube online video play, up to 1080P, HTML5, Flash10.1.
Picture	Supports JPG, BMP, PNG, etc. automatic rotation.
Power Adapter	input AC90~230V 50/60Hz
Speaker	2x5W
Operation System	Android 4.2、 4.4、 5.1.
Language	Multiple languages.
System Management	Supports OTA remote upgrade, disk upgrade.
	The Unmodified "Vanilla Android" system with open root privileges

# Datasheet - *Permaplay*

## Dimension:

