# Datasheet - Permaplay

### P14KDTAB02NS 13, 3" android display





#### **Product Specification**

| CPU                     | Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764                          |
|-------------------------|---|
| Frequency               | 2.2 GHz   |
| RAM                     | DDR3 2G default/4G (upgradable)   |
| Internal Storage        | EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.                |
| Resolution/Aspect Ratio | 1366x768/16:9   |
| Viewing Angle           | 45/45/20/45   |
| Network Support         | With RJ45 port, supports 10/100/1000M Ethernet.                               |
|                         | Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0. |
| Clock                   | Built-in battery power supply.  |
| User Interface          | USB 2.0Host x2  |
|                         | TF card, supports up to 32GB  |
|                         | HDMI 2.0 input.   |
| Hardware Keys           | 7 Buttons ( Menu /Esc/Vol-/Vol+/Next/Prev/Enter)                              |
| Stereo Speaker          | 3Wx2  |
| Brightness              | 220 nits  |
| Contrast                | 500:1   |
| Lifetime                | 20000 hrs   |
| Audio                   | MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP                                     |
| Video                   | H.264, MPEG2, VP6, VP8, MVC 2160P@24FPS.                                      |
|                         | YouTube online video play, up to 1080P, HTML5, Flash10.1.                     |
| Picture                 | Supports PNG,BMP,JPG  |
| Power Adapter           | Input: AC100-240V.50-60HZ Output: DC12V 3A.                                   |
| Operation System        | Google Android 6.0  |
| Language                | Multiple languages.   |
|                         | Supports OTA remote upgrade, disk upgrade                                     |

## Datasheet - Permaplay

| System Management   | Open root privileges  |
|---------------------|---|
|                     | Customizable local or remote server management system.            |
|                     | Supports multiple serial devices, USB devices, IO control devices |
| Wall mount          | VESA 75mm   |
| Weight              | 1.0Kg   |
| Operation Condition | 0°C~40°C  |
| Storage Condition   | -20°C~55°C  |

#### **Dimension:**



