

## P55KDTAB02NS

## 55" android display



### Product Specification

CPU	Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764
Frequency	2.2 GHz
RAM	DDR3 2G default/4G (upgradable)
Resolution/Aspect Ratio	1920x1080/16:9
Viewing Angle	89/89/89/89
Internal Storage	EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.
Network Support	With RJ45 port, supports 10/100/1000M Ethernet. Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0.
Clock	Built-in battery power supply.
User Interface	USB 2.0 Host x2 TF card, supports up to 32GB
Hardware Keys	7 Buttons ( Menu /Esc/Vol-/Vol+/Next/Prev/Enter)
Stereo Speaker	10Wx2
Brightness	300nits
Contrast	1200:1
Lifetime	30000 hrs
Audio	MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP
Video	H.264, MPEG2, VP6, VP8, MVC 2160P@24FPS. YouTube online video play, up to 1080P, HTML5, Flash10.1.
Picture	Supports PNG,BMP,JPG
Power Adapter	Input: AC100-240V.50-60HZ
Operation System	Google Android 6.0
Language	Multiple languages.
System Management	Supports OTA remote upgrade, disk upgrade Open root privileges

# Datasheet - *Permaplay*

	Customizable local or remote server management system.
	Supports multiple serial devices, USB devices, IO control devices
Wall mount	VESA 400mm
Weight	9.2Kg
Operation Condition	0°C~40°C
Storage Condition	-20°C~55°C

## Dimension:

